

# Cheenar

## Paints

**CHEENAR PAINTS MANUAL**

**AND PRODUCT LIST**

**SHEGAL**

*Paints Industry  
Kabul Afghanistan*



[shegal\\_paints@gmail.com](mailto:shegal_paints@gmail.com)

## **ABOUT SHEGAL PAINTS INDUSTRY**

The company Shegal Paints Industry was founded in 2022. Shegal paint industry is an Afghani Paint Industry, engaged in the production and sale of building, industrial, decorative paints, and furniture paints. We offer our products and services both through a broad nationwide network of partners and alternative distribution channels. Shegal's considerable experience and contribution guarantee the satisfaction of the needs of the climatic, housing, and construction infrastructures of the overall ecosystem concerning paints in Afghanistan. At the same time, we aim at the continuous expansion of activities by innovative and ecological products, both in Afghanistan and abroad. Shegal has a passion for paints and that is why we have been able to supply the Afghanistan market with high-quality products for years. Fortunately, Shegal paints industry has obtained ISO 9001:2015 Quality Management Certificate.

### **VISION**

Our vision is through our company's operation to create the conditions for a better quality of life for our clients and staff, having as the primary task to support a sustainable environment for us and future generations.

Our company offers to our lives as well as to the community, of which we are part. To develop business practices that will promote the development of the size of our company as well as our operation throughout Afghanistan.

### **MISSION**

Our mission is to produce and distribute high-quality paints to provide the ideal solution for any project budget with products meeting the needs of our customers by creating ideal living and working spaces.

# SHEGAL PAINTS INDUSTRY

## TECHNICAL DATA SHEET

جمهوری اسلامی افغانستان  
وزارت صنعت و تجارت  
ریاست عمومی ثبت مرکزی و مالکیت فکری



د افغانستان اسلامي جمهوریت  
د صنعت او سوداګرۍ وزارت  
د مرکزي ثبت او فکري مالکیت لوی ریاست

Reg #: 157104  
License #: 82133

Islamic Republic of Afghanistan  
Ministry of Industry and Commerce  
General Directorate of Central Business Registry & Intellectual Property

د ثبت نمبر: ۱۵۷۱۰۴  
د جواز نمبر: ۸۲۱۳۳

TIN / نمبر تشخیصیه مالییه / 9016144181



**جواز ثبت**  
**Business License**

شرکت تولیدی رنگ تعمیرات شیگل  
Shegal paints Building production Company



V-President / مرستیال / کفایت الله صافی  
kefayatullah Safi



President / رئیس / شاکر الله سادقی  
Shakirullah Sadiqi

تصدیق کوي دا جواز چې نوم یې پورته یاد شوی دی د محدودالمسولیت شرکتونو د قانون او د افغانستان د نورو نافذه قوانینو پر بنسټ ثبت او صادر شو. تصدیق میگردد این جواز که نام آن در فوق ذکر میباشند، در مطابقت با قانون شرکتهاى محدودالمسولیت و سایر قوانین نافذه افغانستان ثبت و صادر گردیده است.

**It is certified that this license with mentioned name, is registered and issued in accordance with and subject to the LLC and other effective laws of Afghanistan.**

Issue Date: 05/Sep/2023 ۱۴۰۲/۰۶/۱۳ د صدور نېټه:  
Valid Date: 04/Sep/2026 ۱۴۰۵/۰۶/۱۳ د پای نېټه:  
Established: 2022 ۱۳۰۱ د تاسیس کال:  
سکتور فعالیت: تولیدی رنگ تعمیرات  
ادرس شرکت: سرک بهمان قلعه وزیر، مرکز کابل، کابل



مولوی محمد حایم "مستعین"  
د مرکزی ثبت اداره  
Mawlawi Mohammad Halim Mustaeen  
Authorized Signature

نمبر سلسله: A00016264  
قیمت حق الطبع: (۵۰۰) افغانی

جمهوری اسلامی افغانستان  
وزارت صنعت و تجارت  
ریاست عمومی پارکهای صنعتی و امور صنایع



د افغانستان اسلامي جمهوریت  
د صنعت او سوداګرۍ وزارت  
د مرکزي ثبت او فکري مالکیت لوی ریاست

نمبر جواز: 82133

**شرکت تولیدی رنگ تعمیرات شیگل**

نمبر ثبت: 286

تصدیق کوي چې شرکت چې نوم یې پورته یاد شوی دی د محدودالمسولیت شرکتونو د قانون او د افغانستان د نورو نافذه قوانینو پر بنسټ ثبت او صادر شو. تصدیق میگردد این جواز که نام آن در فوق ذکر میباشند، در مطابقت با قانون شرکتهاى محدودالمسولیت و سایر قوانین نافذه افغانستان ثبت و صادر گردیده است.

**This is to certify that the mentioned company is registered in the Industrial and Manufacturing Companies System and is entitled to its rights.**

Issue Date: 2023-11-17 ۱۴۰۲/۰۹/۲۶ تاریخ صدور:  
Valid Date: 2028-10-17 ۱۴۵۰/۰۹/۲۶ تاریخ منتهی:  
سال تاسیس: 2022



Reg. No: 28457  
Reg. Date: 2024/11/28



د افغانستان اسلامي جمهوریت  
د صنعت او سوداګرۍ وزارت  
د مرکزي ثبت او فکري مالکیت لوی ریاست

نمبر جواز: 28457  
نمبر ثبت: ۱۴۰۲/۱۱/۲۸

ISLAMIC REPUBLIC OF AFGHANISTAN  
MINISTRY OF INDUSTRY & COMMERCE  
CENTRAL BUSINESS REGISTRY & IP  
Afghanistan Patent & Trademark Office (APTO)

د ثبت شمېره: ۲۸۴۵۷  
د ثبت نېټه: ۱۴۰۲/۱۱/۲۸

**تصدیقنامه ثبت علامه تجاری / Trademark Registration Certificate / د سوداګرۍ ثبت د ثبت تصدیق پاته**

په دې توګه تصدیق کوي چې کسب شوی سوداګریزه ثبت د ۱۴۰۲/۱۱/۲۸ نېټې د ۱۹۹۵ کال پورته په اساس د لاندې ذکر شوی حرکت/نښه په نوم سوداګریزه ثبت د ثبت د قانون د ۱۹ او ۲۰ څارونو بنسټ کېښود او د ثبت کولو نېټه د ۱۴۰۲/۱۱/۲۸ نېټې په د اعتبار موده خلاصی او همدارنګه د علامه پورته یاد په ۱۹۵۳ کچه رسې چېرته ثبت کوي خبره شوی دی.

دین ورسره تصدیق میگردد که علامت تجاری ثبت شوی د فورې افهروانه شماره ۱۹۹۵ تاریخ ۱۴۰۲/۱۱/۲۸ په نام حرکت/نښه په دې اړخ اسم آن ذکر کېږدنه است. طبق ماده ۱۹ او ۲۰ قانون ثبت علامه تجاری ثبت وړای حالت ده ساتل موند. حمایت فرد داشته و میعاد جاهیه آن تاریخ ۱۴۱۹/۱۱/۱۹ منطقی خواهد شد. همدمان جهت اطلاع صاحب علامه به شماره ۱۹۵۳ جوبده جسی اثر شتر.

**This is to certify that printed trademark for the under said company/person has been registered as per application number 28654 dated 2024/09/10 and is issued under Articles 19 & 20 of Law on Trademarks Registration for the period of 10 years and will expire on 2034/09/09. It has been published on official gazette No 1454 for public information.**

شرکت تولیدی رنگ تعمیرات شیگل  
Shegal paints Building production company (مرکز کابل)



**CHEENAR**



طبقه/طبقان: 2 - شامل رنگ تعمیرات میباشند



## Certificate of Registration

This is to certify that the  
**Quality Management System**  
of  
**SHEGAL PAINTS BUILDING PRODUCTION COMPANY**  
at  
**QALA-E- WAZIR, PAGHMAN ROAD, KABUL, AFGHANISTAN**

has been independently assessed and is  
compliant with the requirements of:

**ISO 9001:2015**

For the following scope of activities:

**MANUFACTURER OF PAINTS AND COATINGS**

**Certificate Number: UQ - 2025041909**

Validity of this certificate can be verified at [www.ukcertifications.org.uk/verify](http://www.ukcertifications.org.uk/verify)

Date of Certification	19th April 2025
1 <sup>st</sup> Surveillance Audit Due	18th April 2026
2 <sup>nd</sup> Surveillance Audit Due	18th April 2027
Certificate Expiry	18th April 2028

*Daniel..*  
Authorised Signatory



This certificate is the property of UK Certification & Inspection Limited and shall be returned immediately on request.  
71-75 Shelton Street, Covent Garden, London, WC2H 9JQ, United Kingdom  
Website:- [www.ukcertifications.org.uk](http://www.ukcertifications.org.uk), email:- [info@ukcertifications.org.uk](mailto:info@ukcertifications.org.uk)  
Company No. 11847851

# Cheenar Weather Shield



## Description

**CHEENAR WEATHER RESIST** is a premium matt 100% acrylic paint for exterior use. Suitable for new or old surfaces requiring frequent repainting, e.g. public buildings, hotels, hospitals, schools, etc. Features high water-repellency, excellent opacity and surface coverage, as well as outstanding resistance to weather conditions and aging. Provides excellent workability and flow while having quick-drying time. Being vapor-permeable, it allows high building breathability. Offers strong adhesion to any type of new or old substrate. Delivers a flawless matt finish.

## Field of Application

**CHEENAR WEATHER RESIST** is used for exterior use on all common building materials, including concrete, render, bricks, gypsum boards, asbestos cement, wood, etc.

It constitutes an economic and reliable solution for painting.

## Direction for Use

### 1. Substrate preparation:

The substrate should be dry and free of grease, loose particles, dust, etc.

- Cracks or joints are filled with CHEENAR acrylic based 100 % filling.
- Any imperfections in concrete should be patched with cement, while imperfections in exposed concrete should be plastered.

• Plastered walls should be primed with the water-based primer 100% Acrylic, thinned up to 50% with clean water. These primers are also ideal to use for stabilization of loose or crumbly substrates.

In case you are going to paint with dark colors, it is recommended to apply a coat of CHEENAR ACRYLIC BASED PRIMER tinted in a light shade of the same color tone on a base with higher opacity.

### 2. Application:

Before use, CHEENAR ACRYLIC BASED PRIMER should be thoroughly stirred and applied as is or thinned by 40-45% with clean water. Two coats of CHEENAR ACRYLIC BASED PRIMER are applied with a roller, brush, or airless gun. The second coat is applied after the first one has completely dried. Temperature during application and drying of the paint should be between +10°C and +35°C.

## Coverage

CHEENAR WEATHER SHIELD covers approx. 13-15 m<sup>2</sup>/lit per coat, on previously prepared surfaces.

## Packing

CHEENAR WEATHER SHIELD is supplied in 1 lit and 4 lit containers.

## Shelf Life - Storage

24 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

**Tools Clearing: Clear all equipment with mineral water**



# CHEENAR SUPER EMULTION



## Description

**CHEENAR SUPER EMULTION** is a premium matt emulsion paint with exceptional durability, for use on interior walls and ceilings. Suitable for new or old surfaces requiring frequent repainting, e.g. public buildings, hotels, hospitals, schools, etc. Features excellent surface coverage and opacity while offering great workability and flow. Has quick-drying and recoat times. Provides strong adhesion to any type of new or old substrate. Dries quickly to a beautiful matt finish. Nearly odorless.

## Field of Application

**CHEENAR SUPER EMULTION** is used for indoor applications, on new or old surfaces, on common building materials such as concrete, plaster, gypsum boards, etc.

It constitutes an economic and reliable solution for painting.

## Direction for Use

### 1. Substrate preparation:

The substrate should be dry and free of grease, loose particles, dust, etc.

- Cracks or joints are filled with CHEENAR acrylic based 100 % filling.
- Any imperfections in concrete should be patched with cement, while imperfections in exposed concrete should be plastered.

The substrate should be primed with the concentrated, acrylic water-based primer CHEENAR PRIMER, thinned with clean water. Loose or crumbly substrates should be primed with the water-based primer 75% PRIMER, thinned up to 50% with clean water. Surfaces stained by smoke, nicotine, exhaust fumes, water-soluble markers, pencils, etc. should also be primed. Priming is not necessary on already painted surfaces as long as the old paint is sound.

### 2. Application

**CHEENAR SUPER EMULTION** should be thoroughly stirred before use. It is applied as is or thinned 5-10% with clean water. **CHEENAR SUPER EMULTION** is applied in two coats with a roller, brush, or airless gun. The second coat is applied once the first coat has completely dried.

## Coverage

**CHEENAR SUPER EMULTION** covers approx. 13-15 m<sup>2</sup>/lit per coat, on previously prepared surfaces.

## Packing

**CHEENAR SUPER EMULTION** is supplied in 0.91 lit, 3.64 and 14.56 lit containers.

## Shelf Life - Storage

24 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

**Tools Clearing: Clear all equipment with mineral water**



# CHEENAR WALL PUTTY



### Description

**CHEENAR WALL FILLING** is a ready-mixed water based filler, suitable for skim coating interior surfaces. It is easy to spread and can be sanded down to a smooth, level surface, ready for priming and painting.

### Field of Application

**CHEENAR WALL FILLING** is ideal smoothing and preparing surfaces of plaster, concrete, masonry, wood, gypsum board and cement board.

### Direction for Use

#### 1. Substrate preparation:

The substrate must be stable and free of dust, grease, loose particles, etc.

- Cracks or joints are filled with cement
- Any imperfections in concrete should be patched with cement, while imperfections in exposed concrete should be plastered.

The substrate should be primed with the acrylic water-based primer CHEENAR PRIMER.

#### 2. Application

**CHEENAR WALL FILLING** is applied by trowel using a dragging technique in two coats. The second coat follows after the first has dried. After drying, the treated surface is smoothed down with sandpaper prior to painting and painting.

### Coverage

1.5-2.5 kg/m<sup>2</sup>, depending on coat thickness.

### Packing

**CHEENAR WALL FILLING** is supplied in plastic containers of 5 Kg and 20 Kg.

### Shelf Life - Storage

12 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

**Tools Clearing:** Clear all equipment with mineral water





# Cheenar 100% Acrylic Primer

## Description

**CHEENAR 100% Acrylic PRIMER** is a white, ready-to-use, acrylic, water-based primer for gypsum boards to be painted over with water-based emulsion or acrylic paints. Promotes good adhesion of paints to gypsum boards and improves their hiding power, ensuring surface coverage with just one coat while reducing the costs of the entire process. Nearly odorless, and environment and user-friendly.

## Field of Application

**CHEENAR 100% Acrylic Primer** is used as a ready-to-use primer used to ensure adhesion and high opacity of water-based paints to gypsum boards.

## Direction for Use

### 1. Substrate preparation:

The surface to be primed must be dry and free of dust, grease, and other contaminants. It is recommended to prepare and smooth the gypsum boards with the special gypsum board filler.

### 2. Application

**CHEENAR 100% Acrylic Primer** is well-stirred and uniformly applied over the substrate with a brush, roller or spray in one coat. If a very smooth surface is desired, the primed surface should be sanded with fine sandpaper. After the dust is removed, the selected paint can be applied.

## Coverage

13-15 m<sup>2</sup>/lit depending on substrate absorbency.

## Packing

**CHEENAR 100% Acrylic PRIMER** is supplied in plastic containers of 4 lit and 16 lit.

## Shelf Life - Storage

24 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

**Tools Clearing:** Clear all equipment with mineral water





# Cheenar Synthetic Enamel

## Description

**CHEENAR SYNTHETIC ENAMEL** is a premium enamel paint for use on new or old metal surfaces. It features high hardness and surface coverage while showing excellent durability against weather conditions and aging. It dries quickly to a gloss, highly wear- and impact-resistant final surface. Suitable for interior and exterior use.

## Field of Application

**CHEENAR SYNTHETIC ENAMEL** is used for indoor or outdoor applications, on new or old metal surfaces, such as doors, railings, machinery and tools.

## Direction for Use

### 1. Substrate preparation:

The substrate should be dry and free of dust, oil, grease, loose particles, etc., while any imperfections should be smoothed down with sandpaper. The surface is then primed with **CHEENAR-RUST PRIMER**. For application to galvanized metal or aluminum, priming with EPOXY is necessary to achieve maximum adhesion. After 24 hours, provided the primer has completely dried, the first coat of **CHEENAR SYNTHETIC ENAMEL** can be applied.



### 2. Application

Stir **CHEENAR SYNTHETIC ENAMEL** well before use. For brush or roller application, thin up to 5% with **CHEENAR TAPIN OIL**, and for airless spray application thin 10- 20% with **CHEENAR TARPIN OIL**. Apply two coats allowing the first coat to dry completely before applying the second, after approximately 24 hours. Temperature during application and drying of the paint should range between +10°C and +35°C.

## Coverage

**CHEENAR SYNTHETIC ENAMEL** covers approx. 12-15 m<sup>2</sup>/lit per coat, on previously prepared surfaces.

## Packing


**CHEENAR Synthetic Enamel** is supplied in 0.91 lit and 3.64 lit containers.

## Shelf Life - Storage

24 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

**Tools Clearing:** Clear all equipment with Cheenar tarpin oil.





# Cheenar Clear Lacquer

## Description

**Cheenar Lacquer** is premium clear wood preservative and protective impregnation. Thanks to its deep penetrating action, it protects against wood rot, woodworm, fungi, and blue stain. Shows resistance to weather conditions and aging and does not peel or swell. Easy to work with and can be painted over. Suitable for exterior use.

## Field of Application

Suitable for all exterior woodwork, e.g. doors, windows, wooden constructions, garden furniture, etc., to protect from woodworm, fungi, blue stain, or decay while bringing out the natural beauty of the wood piece.

## Direction for Use

### 1. Substrate preparation:

The substrate should be dry and free of grease, dust, etc., while any imperfections should be rubbed down with sandpaper.

### 2. Application

Stir **Cheenar Lacquer** well before use. Apply undiluted with a brush or airless gun in two or three coats. Each new coat is applied as soon as the previous one has completely dried. Temperature during application and drying of **Cheenar Lacquer** should be between +10°C and +30°C.

## Coverage

12-15 m<sup>2</sup>/lit, depending on the hardness of the wood.

## Packing


**Cheenar Lacquer** is supplied in containers of 0.75 lit and 3 lit.

## Shelf Life - Storage

24 months from production date if stored in original, unopened packaging, in cool, shady and well-ventilated spaces, at temperatures between +5°C and +35°C, away from materials that may cause oxidation. Protect from direct sunlight and frost.

**Tools Clearing:** Clear all equipment with Cheenar Thinner while lacquer is still fresh.





# Cheenar Clear Varnish

## Description

**Cheenar Clear Varnish** is a transparent, two-component polyurethane varnish. The membrane it forms is watertight and resistant to UV radiation; it has great mechanical and chemical resistance.

It offers the following advantages:

- Easy application
- Resistance to UV radiation and weather conditions (rain, frost)
- Resistance to detergents, oils, seawater, alkalis
- Vapor permeability
- Resistance to pedestrian traffic and light vehicular traffic

## Field of Application

**Cheenar Clear Varnish** is suitable for waterproofing and protection of:

- Decorative micro cement coatings
- Concrete
- Natural stone
- Wood
- Metal surfaces
- Epoxy coatings (e.g. as protection of epoxy coat inside swimming pools). It provides resistance to chalking and discoloration, caused by UV radiation.

## Direction for Use

### 1. Substrate preparation:

The substrate should be dry and free of grease, dust, etc.

### 2. Application

Stir **CHEENAR Clear Varnish** before use. It is applied by roller, brush, or airless gun. Depending on the porosity and intended use of the substrate, 2-4 coats are required. Each coat is applied within 24 hours from the previous one, depending on the weather conditions.

## Coverage

**CHEENAR Clear Varnish** 12-15m<sup>2</sup> /lit per coat, depending on the porosity of the substrate.

## Packing

**CHEENAR Clear Varnish** is supplied in 0.75 lit and 3 lit containers.

## Shelf Life - Storage

24 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

**Tools Clearing:** Clear all equipment with Cheenar Tarpin while varnish is still fresh.





# Cheenar Thinner

## Description

**Cheenar Thinner** is a specially formulated solvent blend of aliphatic hydrocarbons, esters and ketones.

## Field of Application

**Cheenar Thinner** is specifically designed for thinning all kinds of **Cheenar** enamel paints and Lacquer. Suitable for thinning solvent-based enamel paints to be applied by airless spray gun. Also effective for cleaning application tools. Thanks to its special formulation, **Cheenar Thinner** allows for quick drying of the paint.

## Direction for Use

Before using **Cheenar Thinner**, check the recommended thinning ratio of the product to be used. Then, add the required amount of **Cheenar Thinner** and stir until you get a homogeneous consistency.

## Coverage

Consumption varies depending on the nature of the application.

## Packing

**Cheenar Thinner** is supplied in containers of 0.91 lit and 3.64 lit.

## Shelf Life - Storage

36 months from production date, in original, sealed containers, stored at temperatures above 5°C and protected from high temperatures (<+30°C).

## Remarks

- Ensure adequate ventilation when applying **Cheenar Thinner** indoors.
- Keep away from sources of ignition during application – No smoking.
- Please consult the directions for safe use and precautions written on the packaging before use.



**Make Your Life Colorful**

**With**

**Shegal Paints**

**Industry**

*Your Satisfaction helps us to perfection*

## Table of Content

<b>About Us .....</b>	<b>Page 1</b>
<b>Cheenar Weather Shield .....</b>	<b>Page 2</b>
<b>Cheenar Super Emulation .....</b>	<b>Page 3</b>
<b>Cheenar Wall Putty .....</b>	<b>Page 4</b>
<b>Cheenar 100 % Acrylic Primer .....</b>	<b>Page 5</b>
<b>Cheenar Synthetic Enamel .....</b>	<b>Page 6</b>
<b>Cheenar Clear Lacquer .....</b>	<b>Page 7</b>
<b>Cheenar Clear Varnish .....</b>	<b>Page 8</b>
<b>Cheenar Thinner .....</b>	<b>Page 9</b>